
# THE NEW GENERATION OF UNICO®



### **Produced in Italy**

### Maximum acoustic comfort





### Superior energy efficiency

fore, more efficient in all operating areas.



be set to prevent the user from accidentally activating the heating mode.



and marketing products for Air Conditioning, Heating and Air Treatment. The Home of Comfort

www.olimpiasplendid.com









#### **INVERTER RANGE**

# **UNICO EVO-F [PVA]**



#### WITH POST-CONSUMER RECYLED PLASTIC

Front panel made of 100% recycled plastic, in black. A material identical to the original but recovered from post-consumer products. For an increasingly circular economy.

- Inverter motor
- R290 refrigerant gas

16								
02522								
NOM	MAX	NOM	MAX					
1,6kW	2.1kW	1,5kW	2,1kW					
P	A····	A A T						

### **UNICO EVO [PVAN/EVAN]**



The Twin Rotary compressor and latest-generation electronics are synchronised to obtain the best acoustic comfort, in all operating conditions.



•	Inver	ter m	otor

- R290 and R32 refrigerant gas Integrated Wi-Fi

heating. SF function can be set to prevent the user from accidentally activating the heating

20					2	5		30			
02453					024	455		02525			
NOM	MAX	NOM	MAX	NOM	MAX	NOM	MAX	NOM	MAX	NOM	MAX
1,7kW	2.3kW	1,5kW	2,2kW	2,1kW	2,5kW	1,7kW	2,3kW	2,6kW	3,1kW	2,4kW	2,7kW
<u> </u>	A*** ↑ D	<u> </u>	A*** ↑ D	A	A*** ↑ D	<u> </u>	A*** ↑ D	A	A*** ↑ D	A	A*** ↑ D

# **UNICO EVO [EVANX]**

#### WITH AN ADDITIONAL ELECTRIC HEATING ELEMENT

Below a certain outside temperature, the unit automatically switches from heat pump to electric heating to ensure comfort even with the coldest outside temperatures.

Integrated Wi-Fi

R290 refrigerant gas

heating. SF function can be set to prevent the user from accidentally activating the heating

30							
02576							
NOM	MAX	NOM	MAX				
2,6kW	3,1kW	2,4kW	2,7kW				
<u> </u>	A***	A A					

# **UNICO PRO [EVAN]**



#### FOR LARGER ROOMS

Super cooling power to meet the requirements of larger rooms as well.

- Inverter motor
- R32 refrigerant gas
- Integrated Wi-Fi

Mandatory condensation drainage if used for heating. SF function can be set to prevent the user from accidentally activating the heating

	3	0		35				
	02	238		02239				
NOM	MAX	NOM	MAX	NOM	MAX	NOM	MAX	
2,6kW	3,4kW	1,8kW	3,0kW	3,1kW	3,5kW	2,4kW	3,2kW	
A A		A	A*** D	A A T		A A T		


### A UNIQUE **GENERATOR** FOR BUILDING **CLIMATE COMFORT**







### **HEAT RECOVERY VENTILATION AS AN OPTION**



With the dedicated kit, a double-flow HRV unit with heat recovery can be integrated with the Unico Vertical-NK. In addition to the traditional functions of heating and cooling, it can also ensure an efficient and effective air exchange, thus improving indoor air quality and system efficiency.

The HRV unit is equipped with an energy-efficient, cross-flow and counter-flow enthalpy heat exchanger.

#### **ON/OFF RANGE**

